

**Gauge Adaptor SMA-20**

**Direct Gauge Adaptor SMD-20**
**Gauge Adaptor  
SMA-20**
**Direct Gauge Adaptor  
SMD-20**

**A**

Thread	Dimensions (mm/in)		Weight (kg/lbs) ca. per 100	Ordering Codes (Standard Option)
	T	h Hex A		
G1/4	54	19	7,20	SMA-20-G1/4-B-OR-W3
	2.13	.75	15.84	
G1/2	64	27	12,40	SMA-20-G1/2-B-OR-W3
	2.52	1.06	27.28	
1/4 NPT	54	19	7,20	SMA-20-1/4NPT-B-W3
1/2 NPT	64	27	13,50	SMA-20-1/2NPT-B-W3
	2.52	1.06	29.70	
7/16-20 UNF	54	19	7,60	SMA-20-7/16UNF-B-W3
	2.16	.75	16.76	
9/16-18 UNF	57	19	7,50	SMA-20-9/16UNF-B-W3
	2.24	.75	16.53	
G1/4	41	19	5,70	SMD-20-G1/4-B-OR-W3
	1.61	.75	12.54	
G1/2	51	27	10,10	SMD-20-G1/2-B-OR-W3
	2.01	1.06	22.22	
1/4 NPT	41	19	5,80	SMD-20-1/4NPT-W3
1/2 NPT	51	27	12,76	SMD-20-1/2NPT-W3
	2.01	1.06	23.76	
7/16-20 UNF	41	19	6,00	SMD-20-7/16UNF-W3
	1.61	.75	13.20	
9/16-18 UNF	43	19	5,25	SMD-20-9/16UNF-W3
	1.69	.75	11.55	

Standard option - SMA-20: With Hexagon Lock Nut.

Alternative materials and surface finishings are available upon request. Contact STAUFF for further information. Snubber on request.

**Ordering Codes**
**\*SMA\*-20\*-G1/4\*-B\*-OR\*-W3**

* Type	Gauge Adaptor	<b>SMA</b>
* Series	STAUFF Test 20 (Connection Thread M16x2)	<b>-20</b>
* Thread	acc. to dimension table	<b>-G1/4</b>
* Seal Material	NBR (Buna-N®)	<b>-B</b>
	FKM/FPM (Viton®)	<b>-V</b>
	EPDM	<b>-E</b>
* Seal Type	with O-ring	<b>-OR</b>
* Material Code	Steel, zinc/nickel-plated	<b>-W3</b>
	Stainless Steel V2A - 1.4305 (AISI 303)	<b>-W4</b>
	Stainless Steel V4A - 1.4571 (AISI 316 Ti)	<b>-W5</b>

