



## PROJET4200 4200 PSI Pressure Washer Hose

- Tube:** Seamless, black synthetic rubber
- Reinforcement:** One braid of high-tensile steel wire
- Cover:** Wrapped or Smooth abrasion and weather resistant synthetic rubber, Black, Blue or Gray
- Temperature:** -40°C to +121°C/149°C Intermittent (-40°F to +250°F/300° Intermittent)
- Packaging:** 50', 100', 150', 200' in Bulk Reels
- Application:** Pressure wash equipment. All of the hose assemblies shown here are factory made with male NPT end fittings and bend restrictors at each end. One male end is a swivel to prevent hose twisting.
- NOT FOR STEAM SERVICE.**



PART NUMBER	COVER	HOSE I.D.	HOSE O.D.		MAX W.P.	MIN. BEND RADIUS		WEIGHT	ONE PIECE
		(in)	(in)	(mm)	(psi)	(in)	(mm)	(lbs/ft)	COUPLINGS
PJ4-06BK	Wrapped	3/8	0.59	14.99	4,200	2.6	66.0	0.15	E
PJ4-06GY	Wrapped	3/8	0.59	14.99	4,200	2.6	66.0	0.15	E
PJ4-04BLM	Smooth	1/4	0.48	12.19	4,000	2.9	28.3	0.12	E
PJ4-06BLM	Smooth	3/8	0.59	14.99	4,200	2.6	66.0	0.15	E

\*BK indicates the color Black. For other colors add the suffix to the part number as follows:  
GY - Gray, BLM - Blue (Smooth Only).

## PROJET® 4200 4200 PSI Assemblies

PART NUMBER	COLOR	COVER	HOSE SIZE & LENGTH	END 1	END 2	ATTACHING METHOD
PJ4-06BK-050C	Black	Wrapped	3/8" x 50'	3/8" M-NPT Rigid	3/8" M-NPT Swivel	Crimp
PJ4-06BK-100C	Black	Wrapped	3/8" x 100'	3/8" M-NPT Rigid	3/8" M-NPT Swivel	Crimp
PJ4-06GY-050C	Gray	Wrapped	3/8" x 50'	3/8" M-NPT Rigid	3/8" M-NPT Swivel	Crimp
PJ4-06GY-100C	Gray	Wrapped	3/8" x 100'	3/8" M-NPT Rigid	3/8" M-NPT Swivel	Crimp
PJ4-06BLM-050C	Blue	Smooth	3/8" x 50'	3/8" M-NPT Rigid	3/8" M-NPT Swivel	Crimp
PJ4-06BLM-100C	Blue	Smooth	3/8" x 100'	3/8" M-NPT Rigid	3/8" M-NPT Swivel	Crimp

\*4,200 PSI assemblies come with Blue bend restrictors.

\*Call for additional fittings, lengths and assemblies.

